



Skema til forslag til reglementsændringer

Reglementsnummer	Reglements punkt	Side
Tekniske reglement crosskart xtreme	CKX-T 9OTHER CKX-T 9.1	13
Nuværende tekst CKX-T 9OTHER CKX-T 9.1 Minimum weight Ballast: Weights on these shall be maximum 10 kg a piece. Total weight of ballasts max. 35kg 40KG Any ballast weights are required to be solid and uniform and must be mounted to the car's chassis/frame and/or bottom floor and it must be clearly visible. In bottom floor maximum 10 kg is allowed. Ballast must be securely fastened with minimum M6 bolt and locknut x 4 per unit. If ballast is mounted in the floor minimum ø20mm washer shall be used under the floor on both weight and floor. Total maximum ballast weight for bottom plate 20kg. It is recommended to put a thicker/heavier plate to reach the minimum weight. 600cc / 850cc weight with driver min 400kg 750cc weight with driver min 430 kg		
Tekst bør ændres til: CKX-T 9OTHER CKX-T 9.1 Minimum weight Ballast: Weights on these shall be maximum 10 kg a piece. Total weight of ballasts is free Any ballast weights are required to be solid and uniform and must be mounted to the car's chassis/frame and/or bottom floor and it must be clearly visible. In bottom floor maximum 10 kg is allowed. Ballast must be securely fastened with minimum M6 bolt and locknut x 4 per unit. If ballast is mounted in the floor minimum ø20mm washer shall be used under the floor on both weight and floor. Total maximum ballast weight for bottom plate 30kg. It is recommended to put a thicker/heavier plate to reach the minimum weight. 600cc / 850cc weight with driver min 425kg 750cc weight with driver min 460 kg		
Begrundelse: For gøre det mere lige mellem 600/850cc motor og 750 cc motor Man kan se vægten gør fæltet mere lige i rally x selvom man kører med fære heste		
Dette forslag er indsendt af (skal udfyldes): Noah Jørgensen		Dato: 20-07-2024